

SPAN® IMU-HG1900



TACTICAL GRADE MEMS IMU COMBINES WITH SPAN TECHNOLOGY PROVIDING 3D POSITION, VELOCITY AND ATTITUDE



ABOUT SPAN: WORLD-LEADING GNSS+INS TECHNOLOGY

Synchronous Position, Attitude and Navigation (SPAN) technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and Inertial Navigation Systems (INS). The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) measurements combine to provide an exceptional 3D navigation and attitude solution that is stable and continuously available, even through periods when satellite signals are blocked.

SOPHISTICATED, TACTICAL GRADE MEMS PERFORMANCE

The IMU-HG1900 IMU offers a hybrid package of Honeywell's Micro Electromechanical Systems (MEMs) Gyros and RBA accelerometers. Economical, robust and small, the low power IMU-HG1900 provides high end tactical grade performance for commercial and military guidance and navigation applications. When integrated with NovAtel's SPAN technology, this IMU is ideal for airborne and ground applications that require accurate 3D position, velocity and attitude data. The IMU-HG1900 is ITAR controlled and requires export approval for customers outside the United States.

The IMU-HG1900 is available as a complete assembly in an environmentally sealed enclosure. The HG1900 is also available as a stand alone OEM product that can be easily paired with a SPAN enabled GNSS receiver.

IMPROVED ACCURACY

Take advantage of NovAtel CORRECT™ to receive your choice of accuracy and performance, from decimetre to RTK-level positioning. For the most demanding applications, Inertial Explorer® post-processing software from our Waypoint® Products Group offers the highest level of accuracy.

BENEFITS

- + Tactical grade performance
- + Ideal for size constrained applications
- + Easy to integrate with SPAN enabled GNSS receivers

FEATURES

- + MEMS Gyro technology
- + Small size, rugged and light weight
- + 10-34 VDC power input
- + 100 Hz data rate
- + Long MTBF
- + SPAN GNSS+INS functionality

If you require more information about our SPAN products, visit www.novatel.com/span

IMU-HG1900



SPAN SYSTEM PERFORMANCE¹

Horizontal Position Accuracy (RMS)

Single point L1/L2	1.2 m
NovAtel CORRECT	
» SBAS ²	60 cm
» DGPS	40 cm
» PPP ^{3, 4}	
TerraStar-L	40 cm
TerraStar-C	4 cm
» RTK	1 cm + 1 ppm

Data Rate

IMU measurements	100 Hz
INS position	100 Hz
INS velocity	100 Hz
INS attitude	100 Hz

Time Accuracy⁵ 20 ns RMS

Max Velocity⁶ 515 m/s

IMU PERFORMANCE⁷

Gyroscope Performance

Input range	±1000 deg/sec
Rate bias	5 deg/hr
In-run bias stability	1 deg/hr
Rate scale factor	150 ppm
Angular random walk	0.09 deg/√hr

Accelerometer Performance

Range	±30 g
Linearity	500 ppm
Scale factor	200 ppm
Bias repeatability	1 mg
Bias in-run stability	0.7 mg

PHYSICAL AND ELECTRICAL

Dimensions

130 x 130 x 125 mm

Weight

<3.2 kg

Power

Power consumption	7.5 W
Input voltage	+10 to +34 V

Connectors

Power	SAL M12, 5 pin, male
Data	SAL M12, 4 pin, female
Wheel sensor	SAL M12, 8 pin, male

ENVIRONMENTAL

Temperature

Operating	-40°C to +55°C
Storage	-40°C to +80°C

Humidity

MIL-STD-810G,
Method 507.5

Random Vibe MIL-STD-810G,
Method 514.6 (2.0g)

MTBF >20,000 hours

Environment IEC 60529 IP67

INCLUDED ACCESSORIES

- Power cable
- Communication cable
- Wheel sensor cable

OPTIONAL ACCESSORIES

- Mounting plate
- Inertial Explorer post-processing software

For the most recent details of this product:

www.novatel.com/products/span-gnss-inertial-systems/span-imus/span-mems-imus/imu-hg1900

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia
61-400-883-601

Version 1 Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

NovAtel, Inertial Explorer, Waypoint and SPAN are registered trademarks of NovAtel Inc.

NovAtel CORRECT is a trademark of NovAtel Inc.
D21487 September 2016

Printed in Canada.



PERFORMANCE DURING GNSS OUTAGES⁸

Outage Duration	Positioning Mode	POSITION ACCURACY (M) RMS		VELOCITY ACCURACY (M/S) RMS		ATTITUDE ACCURACY (DEGREES) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK ⁹	0.02	0.03	0.010	0.010	0.010	0.010	0.030
	SP	1.00	0.60	0.010	0.010	0.010	0.010	0.030
	PP ¹⁰	0.01	0.02	0.010	0.010	0.005	0.005	0.011
10 s	RTK ⁹	0.12	0.07	0.020	0.010	0.013	0.013	0.036
	SP	1.10	0.65	0.020	0.010	0.013	0.013	0.036
	PP ¹⁰	0.01	0.02	0.010	0.010	0.005	0.005	0.011
60 s	RTK ⁹	1.95	0.30	0.080	0.016	0.018	0.018	0.050
	SP	2.90	0.90	0.080	0.016	0.018	0.018	0.050
	PP ¹⁰	0.10	0.02	0.012	0.010	0.005	0.005	0.014

1. Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

2. GPS-only.

3. Requires subscription to TerraStar data service. Subscriptions available from NovAtel.

4. TerraStar service available depends on the SPAN receiver used. See the receiver product sheet for details.

5. Time accuracy does not include biases due to RF or antenna delay.

6. Export licensing restricts operation to a maximum of 515 metres/second.

7. Supplied by IMU manufacturer.

8. Outage statistics were calculated by taking the RMS of the maximum errors over a minimum of 30 complete GNSS outages. Each outage was followed by 120 seconds of full GNSS availability before the next outage was applied. High accuracy GPS updates (fixed ambiguities) were available immediately before and after each outage. The survey data used to generate these statistics is ground vehicle data collected with frequent changes in azimuth (i.e., as normally observed in ground vehicle environments).

9. 1 ppm should be added to all values to account for additional error due to baseline length.

10. Post-processing results using Inertial Explorer software.